

This call directs the mouse driver to flush (empty) the mouse event queue and the monitor chain data for the session.

Syntax

MouFlushQue (DeviceHandle)

Parameters

;DeviceHandle (HMOU) - input : Mouse device handle from a previous MouOpen.

Return Code

;rc (USHORT) - return:Return code descriptions are: * 0 NO_ERROR *385 ERROR_MOUSE_NO_DEVICE *466 ERROR_MOUSE_DETACHED *501 ERROR_MOUSE_NO_CONSOLE *505 ERROR_MOUSE_EXTENDED_SG

Bindings

C

```
<PRE> #define INCL_MOUSE
USHORT rc = MouFlushQue(DeviceHandle);
HMOU DeviceHandle; /* Mouse device handle */
USHORT rc; /* return code */ </PRE>
```

MASM

```
<PRE> EXTRN MouFlushQue:FAR INCL_MOUSE EQU 1
PUSH WORD DeviceHandle ;Mouse device handle CALL MouFlushQue
Returns WORD </PRE>
```

Mou

From:
<https://www.osfree.ru/doku/> - **osFree wiki**

Permanent link:
<https://www.osfree.ru/doku/doku.php?id=en:docs:fapi:mouflushque&rev=1633614871>

Last update: **2021/10/07 13:54**



