



This is part of **Family API** which allow to create dual-os version of program runs under OS/2 and DOS

**Note:** This is legacy API call. It is recommended to use 32-bit equivalent

2021/09/17 04:47 · prokushev · [0 Comments](#)

2021/08/20 03:18 · prokushev · [0 Comments](#)

## VioEndPopUp

This call is issued by the application when it no longer requires the temporary screen obtained through a previous VioPopUp call.

### Syntax

```
VioEndPopUp (VioHandle)
```

### Parameters

- VioHandle ([HVIO](#)) - input : A reserved word of 0s.

### Return Code

rc ([USHORT](#)) - return:Return code descriptions are:

- 0 NO\_ERROR
- 405 ERROR\_VIO\_NO\_POPUP
- 436 ERROR\_VIO\_INVALID\_HANDLE

### Remarks

When the application issues a VioEndPopUp call, all video calls are directed to the application's normal video buffer.

### PM Considerations

An error is returned if issued with a non-zero handle.

## Bindings

### C

```
#define INCL_VIO

USHORT rc = VioEndPopUp(VioHandle);

HVIO VioHandle; /* Vio device handle */
USHORT rc; /* return code */
```

### MASM

```
EXTRN VioEndPopUp:FAR
INCL_VIO EQU 1

PUSH WORD VioHandle ;Vio device handle
CALL VioEndPopUp

Returns WORD
```

## Related Functions

[VioPopUp](#)

[http://www.edm2.com/index.php/VioEndPopUp\\_\(OS/2\\_1.x\)](http://www.edm2.com/index.php/VioEndPopUp_(OS/2_1.x))

From:  
<https://www.osfree.ru/doku/> - **osFree wiki**

Permanent link:  
<https://www.osfree.ru/doku/doku.php?id=en:docs:fapi:vioendpopup&rev=1634193304>

Last update: **2021/10/14 06:35**

