

This call is issued by the Session Manager when the operator presses PrtSc.

### Syntax

VioPrtSc (VioHandle)

### Parameters

;VioHandle (HVIO) - input: Reserved word of 0s.

### Return Code

;rc (USHORT) - return:Return code descriptions are: \*0 NO\_ERROR \*355 ERROR\_VIO\_MODE \*402 ERROR\_VIO\_SMG\_ONLY \*436 ERROR\_VIO\_INVALID\_HANDLE \*465 ERROR\_VIO\_DETACHED

### Remarks

VioPrtSc supports text modes 0 through 3, and 7. An Alternate Video Subsystem may want to register a replacement for VioPrtSc. An advanced video subsystem could set a graphics mode while the mode known to the base video subsystem PrtSc routine is text. Then, if the operator presses PrtSc, the printer output is unpredictable. VioPrtSc is reserved for use by the session manager. Application programs may not issue VioPrtSc.

Three beeps are generated if a hard error is detected while writing to the printer.

### Bindings

## C

```
<PRE> #define INCL_VIO
USHORT rc = VioPrtSc(VioHandle); HVIO VioHandle; /* Vio handle */
USHORT rc; /* return code */ </PRE>
```

## MASM

```
<PRE> EXTRN VioPrtSc:FAR INCL_VIO EQU 1
PUSH WORD VioHandle ;Vio handle CALL VioPrtSc
Returns WORD </PRE>
```

<http://www.edm2.com/index.php/VioPrtSc>

From:

<https://www.osfree.ru/doku/> - **osFree wiki**

Permanent link:

<https://www.osfree.ru/doku/doku.php?id=en:docs:fapi:vioprtsc&rev=1630822035>

Last update: **2021/09/05 06:07**

