

OS2Server Guide and Reference

Introduction

Goal of OS2Server server is a provide OS/2 Personality on top of L4 microkernel. OS2Server is isolation layer of OS/2 application from another personalities and L4 microkernel itself.

How it organized

OS2Server consist of:

- Configuration file parser
- Set of interfaces to kernel and various servers required to implement OS/2 Personality API

OS2Server uses file provider interface to load config.sys and parses it. While parsing is in progress server loop active already because parsing work in separate thread. Parser thread also starts all RUN and CALL applications pointed in CONFIG.SYS and last task it executes is a PROTSHELL task. CONFIG.SYS stataments processed in folowing way:

1. Skip all BASEDEV stataments
2. Skip all DEVICE stataments
3. Skip all IFS stataments
4. Generate environment according SET stataments
5. Execute all applications pointed by CALL statement
6. Execute all applications pointed by RUN statement
7. Execute application pointed by PROTSHELL statement

Configuration

OS2Server and OS/2 Personality environment configured via text config file named CONFIG.SYS. CONFIG.SYS mostly same as in original OS/2 except some osFree specific things. As example, IFS, BASEDEV and DEVICE statement are ignored because all drivers works in Neutral Personality. Also, additional stataments are supported, like DRIVEMAPPING statement which maps drive letters to Neutral Personality Virtual File System (L4VFS). Here is list of all CONFIG.SYS stataments and variables (most of them not supported yet if no any description of statement here):

- AUTOFAIL
- BUFFERS
- CALL Executes corresponding applications which pointed by this statement.
- CLOCKSCALE
- CLOSEFILES
- CODEPAGE
- COUNTRY
- DEVINFO_KBD
- DEVINFO_VIO
- DISKCACHE
- DLLBASING

- DUMPPROCESS
- EARLYMEMINIT
- FAKEISS
- I13PAGES
- IBM_JAVA_OPTIONS
- IOPL
- IROPT
- JAVANOFPK
- LASTDRIVE
- LDRSTACKOPT
- LIBPATH
- MAXWAIT
- MEMMAN
- MODE
- NDWTIMER
- PAUSEONERROR
- PRINTMONBUFSIZE
- PRIORITY
- PRIORITY_DISK_IO
- PROTECTONLY
- **PROTSHELL** statement containing name of main OS/2 task which executed on OS/2 Personality startup. It can be command line processor, GUI, task manager or any other task which will be starting point for other tasks.
- RASKDATA
- REIPL
- REMOTE_INSTALL_STATE
- RESERVEDRIVELETTER
- RUN Start during startup VIO (not PM) programs after all device statements.
- SETBOOT
- SOURCEPATH
- STRACE
- SUPPRESSPOPUIS
- SWAPPATH
- SXFAKEHWFPU
- SYSDUMP
- THREADS
- TIMESLICE
- TRACE
- TRACEBUF
- TRAPDUMP
- TRAPLOG
- TRUEMODE
- VIRTUALADDRESSLIMIT
- VME
- WORKPLACE_NATIVE
- WORKPLACE_PRIMARY_CP
- WORKPLACE_PROCESS
- WP_OBJHANDLE

In addition to CONFIG.SYS file OS2Server supports some set of command line arguments:

- -s, -server (default=BMODFS) file provider name which used to load CONFIG.SYS
- -n, -name (default=config.sys) file name of configuration file. It can be not CONFIG.SYS, but any pointed here file

Interfaces

```
interface os2server
{
}
```

os2server execution via l4vfs

```
title = os2server demo (l4vfs)
kernel = $(ROOT)/bootstrap -serial
modaddr 0x02000000
module = $(ROOT)/$(ABI)/fiasco -nowait -nokdb -serial -jdb_never_stop -
tbuf_entries=32768 -jdb_cmd=JH
module = $(ROOT)/$(ABI)/sigma0
module = $(ROOT)/$(ABI)/roottask \
task modname "l4io" boot_priority 0xC0 \
task modname "sigma0" boot_priority 0xA0 \
task modname "roottask" boot_priority 0xA0 \
task modname "log" boot_priority 0xC0 \
task modname "simple_file_server" attached 8 modules
module = $(ROOT)/$(ABI)/names
module = $(ROOT)/$(ABI)/log
module = $(ROOT)/$(ABI)/dm_phys
module = $(ROOT)/$(ABI)/simple_ts -t 300
module = $(ROOT)/$(ABI)/rtc
module = $(ROOT)/$(ABI)/l4io --noirq
module = $(ROOT)/$(ABI)/name_server -p
module = $(ROOT)/$(ABI)/simple_file_server -v 12
module = $(ROOT)/$(ABI)/libloader.s.so libloader.s.so
module = $(CFG)/os2-l4vfs.cfg os2-l4vfs.cfg
module = $(ROOT)/$(ABI)/con_demo1 con_demo1
module = $(ROOT)/$(ABI)/con_demo2 con_demo2
module = $(ROOT)/$(ABI)/con_demo3 con_demo3
module = $(ROOT)/$(ABI)/os2server os2server
module = $(CFG)/config.sys config.sys
module = $(ROOT)/$(ABI)/VioWrtTTY_test VioWrtTTY_test
module = $(ROOT)/$(ABI)/fstab -v 12 -b / -m /sfs
module = $(ROOT)/$(ABI)/fprov_proxy
module = $(ROOT)/$(ABI)/l4con --l4io
module = $(ROOT)/$(ABI)/l4exec
module = $(ROOT)/$(ABI)/loader --fprov=fprov_proxy_fs /sfs/os2-l4vfs.cfg
vbeset 0x111

# cfg_os2
```

```
verbose 0
modpath "/sfs"
sleep 0
task "con_demo1" ""
priority 0xA0
task "con_demo2" ""
priority 0xA0
task "con_demo3" ""
priority 0xA0
task "os2server" "--server fprov_proxy_fs --name /sfs/config.sys"
priority 0xA0
```

```
config.sys:
PROTSHELL=/sfs/VioWrtTTY_test
```

From:

<https://www.osfree.ru/doku/> - **osFree wiki**

Permanent link:

<https://www.osfree.ru/doku/doku.php?id=en:docs:os2server&rev=1401474918>

Last update: **2014/05/30 18:35**

