

KbdClose

Bindings: [C](#), [MASM](#)

This call closes the existing logical keyboard identified by the keyboard handle.

KbdClose (KbdHandle)

KbdHandle (**HKBD**) - input Default keyboard or the logical keyboard.

rc (**USHORT**) - return Return code descriptions are:

0	NO_ERROR
439	ERROR_KBD_INVALID_HANDLE
464	ERROR_KBD_DETACHED
504	ERROR_KBD_EXTENDED_SG

Remarks

KbdClose blocks while another thread has the keyboard focus (by way of [KbdGetFocus](#)) until the thread with the focus issues [KbdFreeFocus](#). Therefore, to prevent *KbdClose* from blocking, it is recommended that *KbdClose* be issued only while the current thread has the focus. For example:

- *KbdGetFocus* Wait until focus available on handle 0.
- *KbdClose* Close a logical keyboard handle.
- *KbdClose* Close another logical keyboard handle.
- *KbdClose* Close still another logical keyboard handle.
- *KbdFreeFocus* Give up the focus on handle 0.

C bindings

```
#define INCL_KBD

USHORT rc = KbdClose(KbdHandle);

HKBD      KbdHandle;    /* Keyboard handle */

USHORT    rc;           /* return code */
```

MASM bindings

```
EXTRN KbdClose:FAR
INCL_KBD EQU 1

PUSH WORD KbdHandle ;Keyboard handle
CALL KbdClose
```

Returns **WORD**

□

From:

<https://www.osfree.ru/doku/> - **osFree wiki**

Permanent link:

<https://www.osfree.ru/doku/doku.php?id=en:ibm:prcp:kbd:close>

Last update: **2016/09/15 02:24**

